



## Shield clamp

### PRODUCT DESCRIPTION

By simply pushing the stripped cable in the shield clamp, there is a permanently high and continuous spring pressure of the cable shield.

The contact areas are large, assuring a very good derivation of interference currents.

The HSK shield clamps can be used with the various HEBOCLIPS for assembling 35 mm DIN rails, busbars or direct mounting. The installation of the appropriate shield clamp for the particular cable diameter can be done by tool-free clipping.

### ADVANTAGES

- // permanently high and continuous spring pressure on the cable shield
- // high conductivity

- // very good derivation of high-frequency interferences
- // the six sizes from 1.5 mm to 30 mm shield range can be snapped onto the HEBOCLIP without tools

### TECHNICAL DATA

Material: galvanised spring steel

### ACCESSORIES

- // HEBOCLIP for 35 mm DIN rails
- // HEBOCLIP for direct assembly
- // HEBOCLIP for busbars
- // HEBOCLIP clamp assembly
- // HEBOSET set of assorted fittings

SHIELD CLAMP			
ITEM DESCRIPTION	ORDER NO.	SHIELD DIAMETER	PU
HSK 1,5-3	1010-001	1.5-3 mm	25
HSK 3-6	1010-002	3-6 mm	25
HSK 6-8	1010-003	6-8 mm	25
HSK 8-11	1010-004	8-11 mm	25
HSK 11-16	1010-005	11-16 mm	25
HSK 17-30	1010-017	17-30 mm	25