



Shield clamp Multi

PRODUCT DESCRIPTION

The shield clamp Multi differs from the common shield clamp by the special form of both clamp clips. Due to the resilience of the brackets, a very large clamping range is achieved.

By simply pushing the stripped cable into the shield clamp, the constant spring pressure achieves a good contact surface.

Thereby, because of the extensive contact, a greater reliable conductance of interfering currents is made possible.

The shield clamp Multi can be used with the various HEBOCLIPs for assembly with 35 mm DIN rails, busbars or for direct mounting. The assembly of the suitable shield clamp for a particular cable diameter can be effected by tool-free mounting.

ADVANTAGES

- // fewer stock items due to the large clamping range
- // permanently high and continuous spring pressure on the cable shield
- // high conductance
- // excellent derivation of high-frequency interferences
- // the two sizes can be installed onto the HEBOCLIP without tools

TECHNICAL DATA

Material: galvanised spring steel

ACCESSORIES

- // HEBOCLIP for 35 mm DIN rails
- // HEBOCLIP for direct assembly
- // HEBOCLIP for busbars
- // HEBOCLIP clamp assembly

SHIELD CLAMP MULTI

ITEM DESCRIPTION	ORDER NO.	SHIELD DIAMETER	PU
HSKM 3-12	1011-001	3-12 mm	25
HSKM 7-18	1011-002	7-18 mm	25