



Shield clamp on symmetrical clip foot with double-sided strain relief

PRODUCT DESCRIPTION

The shield clamp on symmetrical clip foot can be snapped onto a 35 mm DIN rail without the use of tools. Just press the cable shield into the shield clamp to achieve a safe contact. The tension relief clamp offers the possibility of reducing strain on the cable sheath by using a cable tie.

- // Clip foot can be dismantled both-sided
- // constant contact with cable shield due to spring pressure
- // excellent conductance of high-frequency interferences
- // double-sided strain relief by using cable ties on the cable sheath

ADVANTAGES

- // easy, tool-free assembly
- // new geometry better compensates tolerances

TECHNICAL DATA

Material: galvanised spring steel

SHIELD CLAMP ON SYMMETRICAL CLIP FOOT WITH DOUBLE-SIDED STRAIN RELIEF			
ITEM DESCRIPTION	ORDER NO.	DETAILED DESCRIPTION	PU
SKHZZ 1,5–3	1032-001C	Shield diameter 1,5–3 mm, with double-sided strain relief	10
SKHZZ 3–6	1032-002C	Shield diameter 3–6 mm, with double-sided strain relief	10
SKHZZ 6–8	1032-003C	Shield diameter 6–8 mm, with double-sided strain relief	10
SKHZZ 8–11	1032-004C	Shield diameter 8–11 mm, with double-sided strain relief	10
SKHZZ 11–16	1032-005C	Shield diameter 11–16 mm, with double-sided strain relief	10
SKHZZ 3–12	1032-011C	Shield diameter 3–12 mm, with double-sided strain relief	10
SKHZZ 7–18	1032-012C	Shield diameter 7–18 mm, with double-sided strain relief	10
SKHZZ 17–30	1032-006C	Shield diameter 17–30 mm, with double-sided strain relief	10