



## Shield clamp for perforated plate with strain relief

### PRODUCT DESCRIPTION

The shield clamp for perforated plate can be snapped onto existing perforated plates with a material thickness of 1.5 mm to 3 mm and a perforation of 8 x 8 mm without the use of tools.

To assure safe contact, the cable shield simply has to be pushed into the shield clamp.

The strain relief clamp provides the possibility of strain relief of the cable sheath by using a cable tie.

### ADVANTAGES

- // tool-free assembly on the perforated plate
- // wide clamping range
- // fewer stock items
- // extremely compact design
- // Strain relief by using a cable tie on the cable sheath

### TECHNICAL DATA

Material: galvanised spring steel

SHIELD CLAMP FOR PERFORATED PLATE WITH STRAIN RELIEF			
ITEM DESCRIPTION	ORDER NO.	DETAILED DESCRIPTION	PU
SKLZ 8/12 1,5-3	1035-031C	Shield diameter 1.5-3 mm, hole spacing 28 mm, with strain relief	10
SKLZ 8/12 3-6	1035-032C	Shield diameter 3-6 mm, hole spacing 28 mm, with strain relief	10
SKLZ 8/12 6-8	1035-033C	Shield diameter 6-8 mm, hole spacing 28 mm, with strain relief	10
SKLZ 8/12 8-11	1035-034C	Shield diameter 8-11 mm, hole spacing 28 mm, with strain relief	10
SKLZ 8/12 11-16	1035-035C	Shield diameter 11-16 mm, hole spacing 28 mm, with strain relief	10
SKLZ 8/12 3-12	1035-042C	Shield diameter 3-12 mm, hole spacing 28 mm, with strain relief	10
SKLZ 8/12 7-18	1035-044C	Shield diameter 7-18 mm, hole spacing 28 mm, with strain relief	10
SKLZ 8/12 17-30	1035-046C	Shield diameter 17-30 mm, hole spacing 28 mm, with strain relief	10
SKLZ 8/10 1,5-3	1035-061C	Shield diameter 1.5-3 mm, hole spacing 42 mm, with strain relief	10
SKLZ 8/10 3-6	1035-062C	Shield diameter 3-6mm, hole spacing 42 mm, with strain relief	10
SKLZ 8/10 6-8	1035-063C	Shield diameter 6-8 mm, hole spacing 42 mm, with strain relief	10
SKLZ 8/10 8-11	1035-064C	Shield diameter 8-11 mm, hole spacing 42 mm, with strain relief	10
SKLZ 8/10 11-16	1035-065C	Shield diameter 11-16 mm, hole spacing 42 mm, with strain relief	10
SKLZ 8/10 3-12	1035-052C	Shield diameter 3-12 mm, hole spacing 42 mm, with strain relief	10
SKLZ 8/10 7-18	1035-054C	Shield diameter 7-18 mm, hole spacing 42 mm, with strain relief	10
SKLZ 8/10 17-30	1035-056C	Shield diameter 17-30 mm, hole spacing 42 mm, with strain relief	10