



Shield clamp riveted on ring cable lug

PRODUCT DESCRIPTION

The cable shield is pressed into the shield clamp and holds independently due to the large clamping force. A short ground connection can be made with a cable strand at the pre-assembled crimp connection. With the strain relief bracket, the cable sheath can be additionally secured by a cable tie.

ADVANTAGES

- // easy handling
- // consistently good contact due to spring pressure
- // very good derivation of high-frequency interference currents

TECHNICAL DATA

- // Material shield clamp: case-hardened spring steel
- // Material ring cable lug: red insulation for wire cross-section 0.5–1.5 mm²

SHIELD CLAMP RIVETED ON RING CABLE LUG WITHOUT STRAIN RELIEF

ITEM DESCRIPTION	ORDER NO.	DETAILED DESCRIPTION	PU
HSK-RKS 1,5–3 R1,5 ²	1016-001C	Shield diameter 1.5–3 mm, wire cross-section 0.5–1.5 mm ²	10
HSK-RKS 3–6 R1,5 ²	1016-002C	Shield diameter 3–6 mm, wire cross-section 0.5–1.5 mm ²	10
HSK-RKS 6–8 R1,5 ²	1016-003C	Shield diameter 6–8 mm, wire cross-section 0.5–1.5 mm ²	10
HSK-RKS 8–11 R1,5 ²	1016-004C	Shield diameter 8–11 mm, wire cross-section 0.5–1.5 mm ²	10
HSKM-RKS 3–12 R1,5 ²	1016-007C	Shield diameter 3–12 mm, wire cross-section 0.5–1.5 mm ²	10

SHIELD CLAMP RIVETED ON RING CABLE LUG WITH STRAIN RELIEF

ITEM DESCRIPTION	ORDER NO.	DETAILED DESCRIPTION	PU
HSK-RKS-Z 1,5–3 R1,5 ²	1016-101C	Shield diameter 1.5–3 mm, wire cross-section 0.5–1.5 mm ²	10
HSK-RKS-Z 3–6 R1,5 ²	1016-102C	Shield diameter 3–6 mm, wire cross-section 0.5–1.5 mm ²	10
HSK-RKS-Z 6–8 R1,5 ²	1016-103C	Shield diameter 6–8 mm, wire cross-section 0.5–1.5 mm ²	10
HSK-RKS-Z 8–11 R1,5 ²	1016-104C	Shield diameter 8–11 mm, wire cross-section 0.5–1.5 mm ²	10
HSKM-RKS-Z 3–12 R1,5 ²	1016-107C	Shield diameter 3–12 mm, wire cross-section 0.5–1.5 mm ²	10