



Shield clamp riveted on ring cable lug

PRODUCT DESCRIPTION

The cable shield is pressed into the shield clamp and holds independently due to the large clamping force. A short ground connection can be made with a cable strand at the pre-assembled crimp connection. With the strain relief bracket, the cable sheath can be additionally secured by a cable tie.

ADVANTAGES

- // easy handling
- // consistently good contact due to spring pressure
- // very good derivation of high-frequency interference currents

TECHNICAL DATA

- // Material shield clamp: case-hardened spring steel
- // Material ring cable lug: yellow insulation for wire cross-section 4.0–6.0 mm²

SHIELD CLAMP RIVETED ON RING CABLE LUG WITHOUT STRAIN RELIEF

ITEM DESCRIPTION	ORDER NO.	DETAILED DESCRIPTION	PU
HSK-RKS 1,5–3 G6 ²	1016-021C	Shield diameter 1.5–3 mm, wire cross-section 4.0–6.0 mm ²	10
HSK-RKS 3–6 G6 ²	1016-022C	Shield diameter 3–6 mm, wire cross-section 4.0–6.0 mm ²	10
HSK-RKS 6–8 G6 ²	1016-023C	Shield diameter 6–8 mm, wire cross-section 4.0–6.0 mm ²	10
HSK-RKS 8–11 G6 ²	1016-024C	Shield diameter 8–11 mm, wire cross-section 4.0–6.0 mm ²	10
HSKM-RKS 3–12 G6 ²	1016-027C	Shield diameter 3–12 mm, wire cross-section 4.0–6.0 mm ²	10

SHIELD CLAMP RIVETED ON RING CABLE LUG WITH STRAIN RELIEF

ITEM DESCRIPTION	ORDER NO.	DETAILED DESCRIPTION	PU
HSK-RKS-Z 1,5–3 G6 ²	1016-121C	Shield diameter 1.5–3 mm, wire cross-section 4.0–6.0 mm ²	10
HSK-RKS-Z 3–6 G6 ²	1016-122C	Shield diameter 3–6 mm, wire cross-section 4.0–6.0 mm ²	10
HSK-RKS-Z 6–8 G6 ²	1016-123C	Shield diameter 6–8 mm, wire cross-section 4.0–6.0 mm ²	10
HSK-RKS-Z 8–11 G6 ²	1016-124C	Shield diameter 8–11 mm, wire cross-section 4.0–6.0 mm ²	10
HSKM-RKS-Z 3–12 G6 ²	1016-127C	Shield diameter 3–12 mm, wire cross-section 4.0–6.0 mm ²	10